

MD500 MECHANICAL SPECIFICATIONS DATA SHEET

Accuracy (per NIST Handbook 44 for Class III devices)

‘All GEC Products are made in the USA’

0 to 2,500 lbs. ± 50 lbs.	± 50 lbs.
2,550 to 10,000 lbs.	± 100 lbs.
10,500 to 20,000 lbs.	± 150 lbs.
Operating Temperature	0 to 120° F
Storage Temperature	-50° F to + 180° F
Power Requirements	None
Options	<ul style="list-style-type: none"> • Available in Kilogram graduation • Available in x 10 lbs. Vernier (MD400C)
Accuracy	1% of applied load
Dimension	
Overall Length	MD500 18 inches
Overall Width	MD500 20 ¼ inches
Height	3 ¼ inches
Weighing Surface	
Length	MD500 13 ½ inches
Width	MD500 14 ¼ inches
Weight	MD500 55 lbs.
Capacity	0 to 20,000 lbs. (0 to 10,000 Kg)

Intrinsically Safe
Unlimited Terrain (5% slope)
Weighable on gravel surface
Roll over protected dial



PROPRIETARY NOTICE

This document contains information which concerns or relates to trade secrets, processes, operations, pricing, style of work apparatus, or to identity, confidential statistical data amount source or any income, profits, losses or expenditures of General Electroynamics Corporation. Such information is being submitted in confidence with the understanding that it will not be disclosed to third parties in whole or part without the express written consent of an officer of General Electroynamics Corp.
 (Reference Trade Sec. Rets Act, 18U.S.C. 1905)

MD 500