

## MD600L DOUBLE-WIDE, FULLY-MECHANICAL SCALE SPECIFICATIONS DATA SHEET

**Accuracy (Per NIST Handbook 44 for Class III devices)**

**“All GEC Products are Made in the USA”**

0 to 2,500 lbs. ± 50 lbs.	± 50 lbs.
2,550 to 10,000 lbs.	± 100 lbs.
10,500 to 20,000 lbs.	± 150 lbs.
Operating Temperature	0°F (-18°C) to + 120°F (49°C)
Storage Temperature	-50°F (-46°C) to + 180°F (82°C)
Power Requirements	Fully Mechanical (No Power Required)
Options	Available in Kilogram Graduation

**Accuracy** +/- 1% of Applied Load

**Dimensions**

Overall Length	18.5” inches
Overall Width	27” inches
Height	1.8” inches

**Weighing Surface**

Length	14.25” inches - with tire roll direction
Width	19.25” inches - perpendicular to tire roll direction
Weight	46 lbs (20.87 kgs)
Capacity	0 to 20,000 lbs (0 to 10,000 Kgs)

**Intrinsically Safe  
 Low profile  
 Fits Tandem tires**

**Rugged design for use in all terrain  
 (5% slope)**

**Reliable on any unimproved surface  
 Magnified lens for readability**

**Accuracy (per NIST Handbook 44 for Class III devices)**



PROPRIETARY NOTICE

This document contains information which concerns or relates to trade secrets, processes, operations, pricing, style of work apparatus, or to identity, confidential statistical data amount source or any income, profits, losses or expenditures of General Electroynamics Corporation. Such information is being submitted in confidence with the understanding that it will not be disclosed to third parties in whole or part without the express written consent of an officer of General Electroynamics Corp.  
 (Reference Trade Sec. Rets Act, 18U.S.C. 1905)

MD600L