

MD600L SPECIFICATIONS DATA SHEET

Accuracy (per NIST Handbook 44 for Class III devices)

0 to 2,500 lbs ± 50lbs.	± 50lbs.
2,550 to 10,000 lbs	± 100lbs.
10,500 to 20,000 lbs	± 150lbs.
Operating Temperature	0 to 120° F
Storage Temperature	-50° F to + 180° F
Power Requirements	None
Options	<ul style="list-style-type: none"> Available in Kilogram graduation

Accuracy 1% of applied load

Dimension

Overall Length	18.5" inches
Overall Width	26.9" inches
Height	1.8" inches

Weighing Surface

Length	14 1/4" inches - with tire roll direction
Width	19 1/4" inches - perpendicular to tire roll direction
Weight	48 lbs.
Capacity	0 to 20,000 lbs. (0 to 10,000 Kg)

Intrinsically Safe

Unlimited Terrain (5% slope)

Low Profile

Dual Wheel

8000 CALENDAR ROAD
 ARLINGTON, TEXAS
 Phone: 817-572-0366
 Fax: 817-572-0373
 Email: info@gecscales.com
 Web: www.gecscales.com
 Movie: <http://impactmovie.com/gec>



PROPRIETARY NOTICE

This document contains information which concerns or relates to trade secrets, processes, operations, pricing, style of work apparatus, or to identity, confidential statistical data amount source or any income, profits, losses or expenditures of General Electroynamics Corporation. Such information is being submitted in confidence with the understanding that it will not be disclosed to third parties in whole or part without the express written consent of an officer of General Electroynamics Corp.
 (Reference Trade Sec. Rets Act, 18U.S.C. 1905)

M
D
6
0
0
L