



# WMS WEIGHT MEASUREMENT SYSTEM

## SPECIFICATIONS DATA SHEET

Operating Temperature	-10 C to 50 C
Storage Temperature	-37 C to -66 C
Internal Power Requirements	7.2 VDC (6x AA NiMH Rechargeable/ Disposable)
External Power Requirements	110/220 VAC, 50/60 Hz

- Options
- Automatic Light Sensor
  - Data Acquisition Interface
  - Seamless Data Transfer
  - Weight Management Software Including Center of Balance
  - Durable Wireless Handheld Unit
  - Detachable Ramps and Spacers
  - Multiple Scale Configuration (2,4,6,8)

### Dimension

Overall Length	14 inches (35.5 cm)
Overall Width	20 ½ inches (52 cm)
Height	3 ¼ inches

### Weighing Surface

Length	10-1/2inches
Width	11 inches
Weight	40 lbs
Capacity	0 to 20,000 lbs ( 0 to 10,000 Kg )



### Features

- Easy Battery Access.
- Pounds or Kilogram Graduations
- User Selectable Increments.
- Waterproof Membrane Switch and Enclosure.
- Foldable Handles for Storage.
- Rugged Design
- Transportable Storage Case

### Accuracy (per NIST Handbook 44 for Class III devices)

0 to 2,500 lbs	± 50lbs.
2,500 to 10,000 lbs	± 100lbs.
10,500 to 20,000 lbs	± 150lbs.

### PROPRIETARY NOTICE

This document contains information which concerns or relates to trade secrets, processes, operations, pricing, style of work apparatus, or to identity, confidential statistical data amount source or any income, profits, losses or expenditures of General Electrodynamics Corporation. Such information is being submitted in confidence with the understanding that it will not be disclosed to third parties in whole or part without the express written consent of an officer of General Electrodynamics Corp.  
(Reference Trade Sec. Rets Act, 18U.S.C. 1905)

WMS